



ANTI-FIRE COMPOSITE

Double Rabbet 20min Fire Rating

Series		ARCHITECTURAL				
FIRE RATING	Label	Warnock Hershey - Intertek / NFPA Compliance				
	Pressure	Neutral & Cat B Positive				
DIMENSIONS	Jamb Thickness (Face)	minimum: 3/4"		maximum: Unlimited		
	Jamb Width (Depth)	Single / Pairs	minimum: 4 - 3/4"		maximum: Equivalent to wall thickness	
	Maximum Opening Sizes	Single	Neutral	Cat A Positive	Cat B Positive	
		Parallel Pair	4'00" x 8'00"	N/A	4'00" x 8'00"	
	Stop	Thickness Minimum: 5/8"		Width Minimum: 1 1/4"		
	Edgebands	Thickness: Equal to Frame Leg		Width Maximum: 3/8" Finished		
CONSTRUCTION	Substrate (Jamb)	Anti-Fire Composite MDF density 45-50 pcf, one piece construction with veneered backface.				
	Stops	Solid Wood 0.36 sg or MDF 45 pcf.				
	Edgeband	Solid Wood 0.36 sg				
	Veneer Grade / Species	"A" & "AA" / Standard, Exotic and Engineered (with restrictions).				
	Factory Finish	UV Cured: Clear, Light, Dark and Custom Stain colors.				
	Laminated Surface	High Pressure Decorative Laminate (with restrictions).				
	Paint Grade Factory Finish	One Piece High Density Fiberboard (HDF) and Paint Grade Veneers. UV Cured: Primed, Standard and Custom Paint colors.				
QUALITY STANDARDS	Adhesive Installation	Type 2 Water Resistance Use a traditional shims system or WSCP Metal Clip System				
	Casing	Standard 2"x 3/8" and 3"x 3/8" MDF, available with wood veneer (same as face), paint grade finish and plastic laminate.				
	Acoustic	Surface applied seals and gaskets only.				
	Quality	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction).				
	Warranty	Interior Use Only (no exterior warranty), 5 years warranty.				
	Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings. Order will not be processed without complete information. Hardware Preps must be revised per listing manufacturing.				

Fire Rated Doors are manufactured per the standards listed on this page. Specifications are subject to the label listing and may change without notice. To ensure please contact your WKS Door Systems representative.